

G

DIRECTIONAL CONTROL VALVES I

Model [Model No.]	Maximum Operating pressure MPa {kgf/cm ² }	Maximum flow rate L/min				Page
		1	10	100	1000	
Low-watt type solenoid valve [LS]	7 {70}	02				G-4
	16 {160}	02				G-4
	16 {160}	03				G-12
Solenoid valve [KSO]	35 {350}	02				G-16
		03				
Minute signal current type solenoid valve [KSOB]	35 {350}	02				G-32
		03				
Solenoid pilot operated directional control valve [JSP]	21 {210}	02				G-34
		03				
Solenoid pilot operated directional control valve [KSH]	35 {350}	04				G-41
	31.5 {315}	06				G-48
	31.5 {315}	10				G-53

Contact Details

Before using the product, please check the guide pages at the front of this catalog.

Internet

<http://www.daikinpmc.com/en/>

For latest information, PDF catalogs and operation manuals

Model [Model No.]	Maximum Operating pressure MPa {kgf/cm ² }	Maximum flow rate L/min				Page
		1	10	100	1000	
Solenoid pilot operated directional control valve [JS]	21 {210} 25 {250}	06				G-58
		10				
Solenoid pilot operated directional control valve [MEP]	21 {210}	12				G-65
		16				
		20				
		25				
		32				
Pilot operated directional control valve [JP]	21 {210}	03				G-71
		06				
		10				
Type C2 solenoid pilot operated directional control valve [C2SW]	25 {250}	03				G-74
		06				
Type C4 solenoid pilot operated directional control valve [C4S]	25 {250}	06				G-78
Seat type solenoid valve [JSC]	25 {250}	01				G-82
Type C2 Seat type solenoid pilot operated directional control valve [C2SL]	25 {250}	03				G-85
		06				
Manually operated valve [DMO]	14 {140}	03				G-90
		06				
Manually operated valve [JM]	21 {210}	02				G-93
Rotary directional control valve [DRO]	7 {70}	02				G-95
Deceleration valve [DDC]	14 {140}	03				G-97
		06				
Cam operated pilot operated valve [DD]	14 {140}	02				G-99